

The RCS Reference Ceiling Speakers are designed to deliver high quality audio performance. The RCS series features polypropylene woofer cones for durability and low distortion. Each speaker has a 1 inch (25mm) silk dome swiveling NEO tweeter that can be aimed at the direction of the listeners for better sound staging.

The RCS-500 speakers have 20% trimmer speaker frame for reduced visibility. Comes complete with paintable rust-resistant grilles, these speakers can be customized to blend with any decor. Installation is quick thanks to a 3-ear Turn 'N' Lock installation mechanism.

## **RCS-500 FEATURES:**

- 1 inch silk dome swivel NEO tweeter
- Bumped back basket and t-yoke for high speaker excursion
- Wider surround for deeper bass and higher speaker excursion
- 12dB/Octave filter network crossover
- Thermal tweeter protection
- Custom compact spring loaded terminals
- Easy to use Turn 'N' Lock installation mechanism
- 20% trimmer speaker frame for better aesthetics
- Printable rust-resistant grille



## **RCS-500** Reference Ceiling Speakers



## **SPECIFICATIONS:**

## **DIMENSIONS:**

| Impedance          | 8-Ohm     |  |
|--------------------|-----------|--|
| Tweeter Size       | 1" (25mm) |  |
| Power Handling RMS | 130 Watts |  |
| Woofer             | 5 1/4"    |  |

**RCS-500** 

| Wooter             | 5 1/4"            |
|--------------------|-------------------|
| Frequency Response | 70Hz - 21kHz      |
| Weight             | 2.48 lbs (1.12kg) |

| Frame diameter        | 8" (203.8mm)   |
|-----------------------|----------------|
| Grille Diameter       | 6 3/4" (172mm) |
| Cut-Out Hole Diameter | 7" (177mm)     |
| Mounting Depth        | 3" (77mm)      |
| Magnet Diameter       | 3 1/8" (80mm)  |



**RCS-500**